

SE-601 B/C

Electrocardiograph



Specification

Physical Specifications	Dimensions	310mm×322mm×101mm
	Weight	3.0kg (Excluding recorder paper and battery)
	Display	5.6 inch, 640×480 multicolor LCD screen. (touch screen as optional).
Power Supply	Mains Supply:	Operating Voltage = 100V-240V Operating Frequency = 50Hz/60Hz Input Current = 0.9-0.4A
	Internal Li-ion Battery Pack:	Rated capacity = 2500mAh (1.5 hours continuous printing, 300 ECG reports) Necessary Charge time: 5 hours
Recording	Recorder:	Thermal dot-matrix recorder
	Printing Density:	8 dots per mm / 200 dots per inch (amplitude axes) 40 dots per mm / 1000 dots per inch (time axes, @ 25 mm/s)
	Recorder Paper:	Folded thermal paper: 110mm×140mm×150pages
	Paper Speed:	5mm/s, 6.25mm/s, 10mm/s, 12.5mm/s, 25mm/s, 50mm/s
	External Printer:	HP1010/1510, HP M401, HP 1020/1020PLUS/1106, HP 2010/1050/2000, HP 2015/2035, HP 1525
HR Recognition	Technique:	Peak-peak detection
	HR Range:	30 BPM ~300 BPM
	Accuracy:	±1 BPM
ECG Unit	Leads:	12 standard leads
	Acquisition Mode:	simultaneously 12 leads
	A/D Converter:	24 bits
	Resolution:	2.52uV/LSB
	Time Constant:	≥3.2s
	Frequency Response:	0.01Hz ~ 300Hz (-3dB)
	Gain:	2.5, 5, 10, 20, 10/5 mm/mV, AGC
	Input Impedance:	≥100MΩ (10Hz)
	Input Circuit Current:	≤0.01μA
	Input Voltage Range:	≤±5 mVpp
	Calibration Voltage:	1mV±2%
	CMRR:	≥140dB (AC on) ≥123dB (AC off)
	Sampling Frequency	16000 Hz

Pacemaker	Amplitude:	±750μV to ±700 mV
	Width:	50μs to 2.0 ms
Filter	AC Filter:	50/60Hz
	DFT Filter:	0.01Hz/0.05Hz/0.15Hz/0.25Hz/0.32Hz/0.5Hz/0.67Hz
	EMG Filter:	Off/25Hz/35Hz/45Hz
	LOWPASS Filter:	300Hz/270Hz/150Hz/100Hz/75Hz
Data Transmission	Report Format:	PDF, XML, DICOM, FDA-SCP
	Data Transmission:	Wi-Fi, Ethernet, RS232
	Data Management System:	SE-1515 Data Management System, bi-directional communication
	HIS connection:	DICOM Worklist/DICOM Storage/HL7/GDT
Wi-Fi (optional)	Transmitting Frequency:	2400-2497MHz
	Frequency Band:	2400-2497MHz
	Modulation Type:	DSSS, CCK, OFDM
	Transmitting Power:	6 - 17dBm
	Effective Radiated Power:	6 - 17dBm
Safety Specifications	Comply with:	IEC 60601-1:2005/A1:2012 EN 60601-1:2006/A1:2013 IEC 60601-1-2:2007 EN 60601-1-2:2007/AC:2010 IEC/EN 60601-2-25
	Anti-electric-shock type:	Class I with internal power supply
	Anti-electric-shock degree:	CF type with defibrillation-proof
	Patient Leakage Current:	NC <10μA (AC) / <10μA (DC) SFC <50μA (AC) / <50μA (DC)
	Patient Auxiliary Current:	NC <10μA (AC) / <10μA (DC) SFC <50μA (AC) / <50μA (DC)
	Environment Specifications	Temperature:
Relative Humidity:		Transport & Storage: 25%~93% Non-Condensing Working: 25%~80% Non-Condensing
Atmospheric Pressure:		Transport & Storage: 70kPa ~106kPa Working: 86kPa ~106kPa